



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 4"		
3-4	4	0.100
11x4.00-4	4	0.150
11x7.00-4	4	0.200
2.5-4	4	0.100
2.80-4	4	0.100
2.8-4	4	0.100
200x50	4	0.050
260x85	4	0.100
3.00-4	4	0.100
3.40-4	4	0.100
3.5-4	4	0.100
4.00-4	4	0.150
4.1/3.50-4	4	0.150
4.10-4	4	0.150
4.1-4	4	0.150
4.8-4	4	0.200
9/3.50-4	4	0.250
9x3.50-4	4	0.100
Rin 5"		
10.00x4.50-5	5	0.150
10.5x5.00-5	5	0.150
11x3.50-5	5	0.100
11x4.00-5	5	0.150
11x4.50-5	5	0.150
11x6.00-5	5	0.200
11x7.00-5	5	0.200
11x7.50-5	5	0.200
13x4.00-5	5	0.150
18x6.5	5	0.300
3.40/3.00-5	5	0.100
3.4-5	5	0.100
3.50-5	5	0.100
3.5-5	5	0.100
4.1/3.50-5	5	0.150
4.10/3.50-5	5	0.150
4.1-5	5	0.150
Rin 5.5"		
14.5x4.5	5.5	0.200

Neumático	Rin	Litros
Rin 6"		
3-6	6	0.100
4-6	6	0.150
8-6	6	0.500
120/70-6	6	0.150
12x6.00-6	6	0.200
12x8.00-6	6	0.250
13x5.00-6	6	0.200
13x6.50-6	6	0.250
14x4.00-6	6	0.150
14x6.00-6	6	0.250
14x8.00-6	6	0.300
15x6.00-6	6	0.250
160/65-6	6	0.250
3.50-6	6	0.150
3.5-6	6	0.150
4.00/3.25-6	6	0.150
4.00-6	6	0.150
4.10/3.50-6	6	0.150
4.1-6	6	0.150
5.30-6	6	0.250
5.3-6	6	0.250
6.90/6.00-6	6	0.350
6.9-6	6	0.350
Rin 7"		
18x7.00-7	7	0.350
4.50-7	7	0.200
4.80-7	7	0.200
Rin 8"		
3-8	8	0.150
4-8	8	0.200
5-8	8	0.250
125/75-8	8	0.200
15x4.50-8	8	0.200
15x6.00-8	8	0.250
16.5x6.50-8	8	0.300
16x5.50-8	8	0.250
16x6.00-8	8	0.250
16x6.50-8	8	0.300



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 8"		
16x6-8	8	0.250
16x7.50-8	8	0.300
170/60-8	8	0.300
17x8.00-8	8	0.350
18.5x8.50-8	8	0.400
18.5x9.50-8	8	0.450
180/70-8	8	0.350
180/70R8	8	0.350
18x11.00-8	8	0.500
18x5.00-8	8	0.250
18x5.70-8	8	0.300
18x6.00-8	8	0.300
18x6.50-8	8	0.300
18x7.00-8	8	0.350
18x8.50-8	8	0.400
18x9.00-8	8	0.450
18x9.50-8	8	0.450
19x7.00-8	8	0.350
2.25-8	8	0.100
2.5-8	8	0.100
20.5x10.00-8	8	0.550
20.5x7.00-8	8	0.400
20.5x8.00-8	8	0.450
20x10.00-8	8	0.550
20x11.00-8	8	0.600
20x12.00-8	8	0.650
20x7.00-8	8	0.400
20x8.00-8	8	0.450
210/60-8	8	0.400
21x10.00-8	8	0.550
21x11.00-8	8	0.600
21x12.00-8	8	0.650
21x7.00-8	8	0.400
22.50x10.00-8	8	0.600
22.5x10.00-8	8	0.600
22x11.00-8	8	0.650
22x9.00-8	8	0.550
25x12.00-8	8	0.800
3.50-8	8	0.150

Neumático	Rin	Litros
Rin 8"		
4.00/2.50-8	8	0.150
4.00/3.00-8	8	0.150
4.00/3.25-8	8	0.150
4.00-8	8	0.200
4.30-8	8	0.200
4.80/3.75-8	8	0.200
4.80/4.00-8	8	0.200
4.80-8	8	0.250
5.00/3.00-8	8	0.200
5.00/3.25-8	8	0.200
5.00-8	8	0.250
5.70/4.50-8	8	0.250
5.70/5.00-8	8	0.3000
5.70-8	8	0.3000
6.00-8	8	0.3500
Rin 9"		
4-9	9	0.200
6-9	9	0.350
20x11.00-9	9	0.600
21.20x7.00-9	9	0.400
21.8x6.00-9	9	0.400
21.9x7.00-9	9	0.450
21x11.00-9	9	0.650
21x12.00-9	9	0.700
21x8.00-9	9	0.450
21x9.00-9	9	0.500
22x12.00-9	9	0.700
23x10.00-9	9	0.650
25x11.00-9	9	0.750
25x12.00-9	9	0.850
25x13.00-9	9	0.900
4.80/4.00-9	9	0.250
4.8-9	9	0.250
5.50/85-9	9	0.300
6.00/4.00-9	9	0.300
6.00-9	9	0.350
6.90-9	9	0.450
6.9-9	9	0.450



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 10"		
04-oct	10	0.250
9-10	10	0.750
15.00-10	10	1.85
18x11.00-10	10	0.550
18x8.00-10	10	0.400
18x9.50-10	10	0.500
195/50B10	10	0.400
20.50-10	10	3.300
20.5x8.00-10	10	0.500
200/50-10	10	0.400
205/50-10	10	0.400
205/65-10	10	0.500
20x10.00-10	10	0.550
20x11.00-10	10	0.650
20x12.00-10	10	0.700
20x5.00-10	10	0.300
20x8.00-10	10	0.450
21.x7.00-10	10	0.450
22x10.00-10	10	0.650
22x11.00-10	10	0.700
22x8.00-10	10	0.500
23.8-10	10	4.4
23.8x6.50-10	10	0.450
23x8.5-10	10	0.600
3x9.00-1	10	0.600
24x11.00-10	10	0.750
27x15.00-10	10	1.15
27x9.00-10	10	0.750
4.00-10	10	0.250
4.50-10	10	0.250
5.00-10	10	0.300
6.50/5.00-10	10	0.400
6.50/5.50-10	10	0.400
6.50-10	10	0.450
6.5-10	10	0.450
7.00/85-10	10	0.450
7.50/5.00-10	10	0.450
7.50/5.50-10	10	0.450

Neumático	Rin	Litros
Rin 10"		
7.50-10	10	0.550
7.5-10	10	0.550
9.00-10	10	0.750
Rin 10.5"		
23.00-10.5	10.5	4.2
Rin 11"		
23.5x8.00-11	11	0.600
23x8.00-11	11	0.600
24x10.00-11	11	0.750
24x9.00-11	11	0.700
Rin 12"		
4-12	12	0.300
5-12	12	0.400
6-12	12	0.500
7-12	12	0.650
8-12	12	0.800
10-12	12	1.1
12-12	12	1.5
10.0/80-12	12	0.950
10.00/75-12	12	0.900
10.00/80-12	12	0.950
10.00-12	12	1.1
11.00/65-12	12	1
155/80-12	12	0.450
170.00/80-12	12	0.550
210.00/65-12	12	0.650
22.00x8.00-12	12	0.600
220/60-12	12	0.650
22x7.50-12	12	0.550
23.00x10.00-12	12	0.800
23.00x10.50-12	12	0.800
23.00x12.00-12	12	0.900
23.00x8.00-12	12	0.650
23.00x8.50-12	12	0.650
23.00x9.00-12	12	0.700
23.00x9.50-12	12	0.750
23.5x8.50-12	12	0.700
23x10.50-12	12	0.800



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 12"		
23x6.00-12	12	0.500
23x8.00-12	12	0.650
23x8.50-12	12	0.650
23x8.5-12	12	0.650
23x9.00-12	12	0.700
24.00x13.00-12	12	1
24x12.00-12	12	0.950
24x12-12	12	1
24x13.00-12	12	1
24x13-12	12	1
25x10.00-12	12	0.850
25x8.00-12	12	1
26.00x12.00-12	12	1.05
26x11.00-12	12	1
26x12.00-12	12	1.05
27.00x10.00-12	12	1
27.00x10.50-12	12	0.950
27.00x8.50-12	12	1
27x10.00-12	12	0.900
3.00-12	12	0.200
3.5-12	12	0.250
32.00x10.5-12	12	1.15
4.00-12	12	0.300
4.50-12	12	0.350
4.5-12	12	0.350
4.80-12	12	0.350
4.8-12	12	0.350
5.00-12	12	0.400
5.30-12	12	0.450
5.3-12	12	0.450
5.70-12	12	0.450
5.7-12	12	0.450
5R12	12	0.350
6.00-12	12	0.500
6.5/80-12	12	0.500
6.5-12	12	0.550
6.9-12	12	0.600
7.00/5.00-12	12	0.550

Neumático	Rin	Litros
Rin 12"		
7.00-12	12	0.650
7.00R12	12	0.550
7.50-12	12	0.700
8.30-12	12	0.850
8.5-12	12	0.850
Rin 13"		
155/80-13	13	0.550
175/80-13	13	0.650
185/80-13	13	0.700
23x5.00	13	0.450
6.00-13	13	0.600
6.50/80-13	13	0.600
6.5-13	13	0.650
Rin 14"		
4-14	14	0.400
5-14	14	0.500
6-14	14	0.650
7-14	14	0.850
11-14	14	1.6
11.00-14	14	1.6
13.00-14	14	2.1
165-14	14	0.750
170/80-14	14	0.700
185-14	14	0.900
195-14	14	0.950
205/75-14	14	0.900
205-14	14	1.050
215/75-14	14	0.950
25x8.50-14	14	0.900
26x11.00-14	14	1.15
26x9.00-14	14	1
4.5-14	14	0.450
6.00-14	14	0.650
7.50-14	14	0.900
7.60-14	14	0.950
8.50-14	14	1.1
8.5-14	14	1.1
9.50-14	14	1.3



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 14"		
9.5-14	14	1.3
Rin 14.5"		
200/60-14.5	14.5	0.850
250/65-14.5	14.5	1.15
Rin 15"		
4-15	15	0.450
5-15	15	0.600
7-15	15	0.950
9-15	15	1.4
10-15	15	1.6
11-15	15	1.8
12-15	15	2.1
10.00/75-15	15	1.35
10.00-15	15	1.6
10.5-15	15	1.7
11.00-15	15	1.8
11.5-15	15	1.95
12.00-15	15	2.1
12.50-15	15	2.2
12.5-15	15	2.2
13.5-15	15	2.4
14.50-15	15	2.6
175/85-15	15	0.850
185/65-15	15	0.850
205/60R15	15	0.950
205/75-15	15	1.05
205/85-15	15	1.1
21.50-15	15	4.2
215/75-15	15	1.1
225/75-15	15	1.15
225/75R15	15	1.15
235/75-15	15	1.25
240/70-15	15	1.25
250/70-15	15	1.3
250/70R15	15	1.3
25x10.50-15	15	1.2
25x12.50-15	15	1.3
25x7.50-15	15	0.900

Neumático	Rin	Litros
Rin 15"		
27x10.50-15	15	1.3
27x13-15	15	1.45
27x8.50-15	15	1.05
27x9.50-15	15	1.2
28x12.00-15	15	1.45
28x12.50-15	15	1.5
28x13.00-15	15	1.5
28x8.5-15	15	1.1
28x9.00-15	15	1.15
29x10.00-15	15	1.3
29x12.50-15	15	1.55
29x8.00-15	15	1.1
29x9.50-15	15	1.25
30x9.50-15	15	1.3
31.00x12.50-15	15	1.65
31.00x13.50-15	15	1.7
31.00x15.50-15	15	1.85
315/70R15	15	1.7
31x10.50-15	15	1.45
31x11.50-15	15	1.55
31x12.50-15	15	1.65
31x12.5-15	15	1.65
31x13.50-15	15	1.7
31x15.00-15	15	1.8
31x15.50-15	15	1.85
32.00x12.00-15	15	1.65
32.00x15.00-15	15	1.9
32x11.50-15	15	1.6
32x12.00-15	15	1.65
32x15.00-15	15	1.9
32x9.50-15	15	1.4
33.00x12.50-15	15	1.75
33x12.00-15	15	1.7
33x12.50-15	15	1.75
33x15.50-15	15	1.95
35.00x11-15	15	1.7
35.00x15.00-15	15	2.1
355/65-15	15	1.9



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 15"		
355/65R15	15	1.9
35x15.00-15	15	2.1
365/80-15	15	2.2
36x11.00-15	15	1.75
36x13.50-15	15	2
38x16.00-15	15	2.3
4.00-15	15	0.450
4.40-15	15	0.500
5.00-15	15	0.600
5.50-15	15	0.650
5.5-15	15	0.650
5.70-15	15	0.700
5.7-15	15	0.700
5.90-15	15	0.750
5.9-15	15	0.750
6.00-15	15	0.750
6.4-15	15	0.850
6.5/80-15	15	0.800
6.50/80-15	15	0.800
6.70-15	15	0.900
6.7-15	15	0.900
7.00/5.50-15	15	0.850
7.00/6.50-15	15	0.900
7.00-15	15	0.950
7.50/5.50-15	15	0.900
7.50-15	15	1.05
7.50R15	15	0.950
7.5L-15	15	0.950
7.60-15	15	1.1
7.6-15	15	1.1
7.75-15	15	1.1
8.25-15	15	1.2
8.25R15	15	1.1
8.5-15	15	1.25
8.55-15	15	1.3
9.5-15	15	1.5
Rin 15.3"		
10.0/75-15.3	15.3	1.4

Neumático	Rin	Litros
Rin 15.3"		
10.00/75- 15.3	15.3	1.4
10.00/85- 15.3	15.3	1.5
10-15.3	15.3	1.65
11.5/80-15.3	15.3	1.75
11.50/80- 15.3	15.3	1.75
12.5/80-15.3	15.3	1.95
260/70-15.3	15.3	1.4
300/80-15.3	15.3	1.8
Rin 15.5"		
280/60-15.5	15.5	1.45
31x15.00- 15.5	15.5	1.9
400/60-15.5	15.5	2.2
500/55-15.5	15.5	2.6
Rin 16"		
8-16	16	1.35
9-16	16	1.55
10.00-16	16	1.8
10.5/65-16	16	1.55
11.00-16	16	2.1
11.20-16	16	2.1
11LR16	16	1.7
12.40-16	16	2.4
12.50-16	16	2.4
13.0/55-16	16	1.8
13.0/75-16	16	2.1
13.50-16	16	2.6
13.60-16	16	2.6
14.0/65-16	16	2.1
200/70R16	16	1.1
215/85-16	16	1.1
225/75-16	16	1.35
225/85-16	16	1.4
235/85-16	16	1.5
240/70R16	16	1.4
245/75-16	16	1.5
245/85-16	16	1.6
255/85-16	16	1.65
260/70R16	16	1.55



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 16"		
265/75-16	16	1.65
280/70-16	16	1.7
280/70R16	16	1.7
315/55R16	16	1.7
340/55-16	16	1.85
4.00-16	16	0.500
4.50-16	16	0.600
5.00-16	16	0.650
5.50-16	16	0.750
6.00-16	16	0.850
6.00R16	16	0.800
6.50-16	16	1
6.60-16	16	1
7.00-16	16	1.1
7.20-16	16	1.5
7.50-16	16	1.2
8.00-16	16	1.35
8.25-16	16	1.4
8.30-16	16	1.4
9.00-16	16	1.6
9.50-16	16	1.7
Rin 16.1"		
11.00-16.1	16.1	2.1
13.50-16.1	16.1	2.6
13.60-16.1	16.1	2.7
14.00-16.1	16.1	2.8
14.5/75-16.1	16.1	2.4
16.50-16.1	16.1	3.3
18.40-16.1	16.1	3.75
21.50-16.1	16.1	4.4
35x19.00- 16.1	16.1	2.5
38x19.00- 16.1	16.1	2.7
38x20.00- 16.1	16.1	2.7
Rin 16.5"		
10.00-16.5	16.5	1.9
10-16.5	16.5	1.9
12.00-16.5	16.5	2.4
12-16.5	16.5	2.4

Neumático	Rin	Litros
Rin 16.5"		
31x10.50- 16.5	16.5	1.7
31x12.00- 16.5	16.5	1.85
33x12.50- 16.5	16.5	2
33x15.00- 16.5	16.5	2.2
33x15.50- 16.5	16.5	2.2
35x14.50- 16.5	16.5	2.3
8.75-16.5	16.5	1.6
9.00-16.5	16.5	1.7
Rin 17"		
10-17	17	2.1
12-17	17	2.5
15.0/55-17	17	2.3
15.00/55-17	17	2.3
19.00/45-17	17	2.5
380/55-17	17	2.3
480/45-17	17	2.5
500/50-17	17	2.8
500/50R17	17	2.8
7.00-17	17	1.25
7.50-17	17	1.4
8.25-17	17	1.6
Rin 17.5"		
10.00-17.5	17.5	2.1
10-17.5	17.5	2.1
11.00-17.5	17.5	2.4
14.00-17.5	17.5	3.15
14-17.5	17.5	3.15
205/65-17.5	17.5	1.35
215/75-17.5	17.5	1.5
225/65-17.5	17.5	1.5
225/70-17.5	17.5	1.55
225/75-17.5	17.5	1.6
235/75-17.5	17.5	1.65
240/55-17.5	17.5	1.5
255/60-17.5	17.5	1.65
255/70-17.5	17.5	1.8
36x16.00- 17.5	17.5	2.6
7.00-17.5	17.5	1.3



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 17.5"		
7-17.5	17.5	1.3
8.00-17.5	17.5	1.7
8-17.5	17.5	1.6
8R17.5	17.5	1.45
9.00-17.5	17.5	1.85
9.5-17.5	17.5	2
Rin 18"		
4-18	18	0.600
7-18	18	1.35
8-18	18	1.65
10-18	18	2.2
12-18	18	2.7
10.00-18	18	2.2
10.5/80-18	18	2.1
10.5/80R18	18	2.1
10.50/80-18	18	2.1
10.50-18	18	2.3
10.5-18	18	2.3
11.00-18	18	2.5
11.50/70-18	18	2.2
12.0/12.5-18	18	2.8
12.0/75-18	18	2.3
12.00/12.50-18	18	2.8
12.5/80-18	18	2.5
12.50/80-18	18	2.5
12.50-18	18	2.8
12.5-18	18	2.8
13.0/65-18	18	2.3
13.00/65-18	18	2.3
13.00-18	18	2.9
14.50/80-18	18	2.9
15.0/70-18	18	2.8
15.00/70-18	18	2.8
15.5/55R18	18	2.5
16.5/80-18	18	3.3
250/80-18	18	1.9
280/70R18	18	2.1
315/80-18	18	2.5

Neumático	Rin	Litros
Rin 18"		
325/70R18	18	2.4
335/80-18	18	2.6
335/80R18	18	2.6
340/65R18	18	2.4
340/80-18	18	2.7
340/80R18	18	2.7
365/70-18	18	2.7
365/70R18	18	2.7
4.00-18	18	0.600
400/70-18	18	2.9
400/70R18	18	2.9
405/70R18	18	2.9
6.00-18	18	1.1
7.00-18	18	1.35
7.50-18	18	1.50
7.5-18	18	1.5
8.25-18	18	1.7
Rin 19"		
4-19	19	0.650
5-19	19	0.900
6-19	19	1.2
7-19	19	1.5
8-19	19	1.75
19R19	19	3.9
4.00-19	19	0.650
4.5-19	19	0.750
6.00-19	19	1.2
Rin 19.5"		
10-19.5	19.5	2.4
15.00-19.5	19.5	3.75
15-19.5	19.5	3.75
16.50-19.5	19.5	4
16.5-19.5	19.5	4
18.00-19.5	19.5	4.4
18-19.5	19.5	4.4
18R19.5	19.5	3.9
19.50-19.5	19.5	4.8
19.5-19.5	19.5	4.8



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 19.5"			Rin 20"		
19.5R19.5	19.5	4.2	11.00R20	20	2.5
225/70-19.5	19.5	1.8	11.20-20	20	2.8
245/70-19.5	19.5	1.95	11.2-20	20	2.8
245/75-19.5	19.5	2	11.2R20	20	2.5
265/70-19.5	19.5	2.1	11.50-20	20	2.9
265/75-19.5	19.5	2.2	12.00-20	20	3.0
285/70-19.5	19.5	2.3	12.00R20	20	2.7
285/75-19.5	19.5	2.4	12.50-20	20	3.15
305/70-19.5	19.5	2.5	12.5-20	20	3.15
305/75-19.5	19.5	2.5	12.5R20	20	2.8
33x16.00-19.5	19.5	2.5	13.00-20	20	3.3
385/65-19.5	19.5	2.9	13-20	20	3.3
40x19.00-19.5	19.5	3.3	14.50-20	20	3.75
435/50-19.5	19.5	2.9	14.5-20	20	3.8
445/55-19.5	19.5	3.2	14.5R20	20	3.30
445/65-19.5	19.5	3.3	15-20	20	3.8
445/65-19.5	19.5	3.3	16.0/70-20	20	3.3
7.00-19.5	19.5	1.55	16.00/70-20	20	3.3
8.00-19.5	19.5	1.85	16.00-20	20	4
8-19.5	19.5	1.85	16/70-20	20	3.3
9.00-19.5	19.5	2.1	16/70R20	20	3.3
9.50-19.5	19.5	2.3	17.5/65-20	20	3.45
9.5-19.5	19.5	2.3	17.50-20	20	4.4
Rin 20"			20.00/70-20	20	4
6-20	20	1.3	20.00-20	20	5
7-20	20	1.6	21.00/80-20	20	4.6
8-20	20	1.9	225/80-20	20	1.95
9-20	20	2.2	260/80R20	20	2.3
10-20	20	2.5	275/80R20	20	2.4
10.00/10.50-20	20	2.5	280/70-20	20	2.3
10.00/6.50-20	20	2.1	280/70R20	20	2.3
10.00/8.00-20	20	2.2	280/85R20	20	2.5
10.00-20	20	2.5	300/70-20	20	2.5
10.30-20	20	2.6	300/70R20	20	2.5
10.50-20	20	2.6	320/70R20	20	2.6
10.5-20	20	2.6	320/85R20	20	2.9
10.5R20	20	2.4	335/80R20	20	2.9
11.00-20	20	2.8	340/80-20	20	3

Tabla de Aplicación OKO México Maquinaria



Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 20"			Rin 20"		
360/70R20	20	2.9	8.3-20	20	2
365/80-20	20	3.15	9.00/6.50-20	20	1.9
365/80R20	20	3.15	9.00-20	20	2.2
365/85-20	20	3.3	9.00R20	20	2
380/70-20	20	3.15	9.50-20	20	2.3
380/75R20	20	3.3	9.50R20	20	2.1
38x14.00-20	20	2.8	9.5-20	20	2.3
395/85-20	20	3.6	Rin 20.5"		
395/85R20	20	3.6	24.00-20.5	20.5	6.25
400/70-20	20	3.3	Rin 21"		
400/70R20	20	3.3	6-21	21	1.35
405/70-20	20	3.3	12-21	21	3.15
405/70R20	20	3.3	12.00-21	21	3.15
41x14.00-20	20	3	14-21	21	3.75
420/75R20	20	3.6	16.00-21	21	4.2
425/75R20	20	3.6	16-21	21	4.2
42x25.00-20	20	3.75	18-21	21	4.8
44x18.00-20	20	3.6	21.00-21	21	5.5
44x18.-20	20	3.6	23.00-21	21	6.25
455/70R20	20	3.6	23-21	21	6.25
460/65-20	20	3.6	24.00-21	21	6.5
47x25.00-20	20	4.2	27.25-21	21	7.25
48x25.00-20	20	4.4	5.00-21	21	1.05
48x26.5-20	20	4.4	6.00-21	21	1.4
48x31.00-20	20	4.6	Rin 22"		
500/45-20	20	3.15	10-22	22	2.8
500/55-20	20	3.45	11-22	22	3
50x20.00-20	20	4.2	12-22	22	3.3
6.50-20	20	1.45	10.00-22	22	2.8
6.5-20	20	1.45	11.00-22	22	3
7.00-20	20	1.60	12.00-22	22	3.3
7.25-20	20	1.65	7.50-22	22	1.95
7.50-20	20	1.75	8.50-22	22	2.3
7.5-20	20	1.8	9.50-22	22	2.6
8.00-20	20	1.9	Rin 22.5"		
8.25/5.50-20	20	1.65	10.00-22.5	22.5	2.8
8.25-20	20	1.95	10-22.5	22.5	2.8
8.30-20	20	2.000	11.00-22.5	23	3.15

Tabla de Aplicación OKO México Maquinaria



Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 22.5"			Rin 22.5"		
11.50-22.5	22.5	3.3	365/70-22.5	22.5	3.45
11-22.5	22.5	3.15	385/65-22.5	22.5	3.45
12.00-22.5	22.5	3.45	400/55-22.5	22.5	3.3
12.50-22.5	22.5	3.6	41x18.00-22.5	22.5	3.6
12.5-22.5	22.5	3.6	425/50-22.5	22.5	3.3
12-22.5	22.5	3.45	425/65-22.5	22.5	3.75
13.00-22.5	22.5	3.75	445/50-22.5	22.5	3.45
14.00-22.5	22.5	4.05	445/65-22.5	22.5	3.9
15.00-22.5	22.5	4.2	445/65R22.5	22.5	3.9
15.50/70-22.5	22.5	3.6	455/55-22.5	22.5	3.75
15.5-22.5	22.5	4.4	500/60-22.5	22.5	4.2
15-22.5	22.5	4.2	500/60R22.5	22.5	4.2
16.00-22.5	22.5	4.6	550/45-22.5	22.5	3.9
16.50/70-22.5	22.5	3.9	550/45R22.5	22.5	3.9
16.5-22.5	22.5	4.8	550/60-22.5	22.5	4.6
16-22.5	22.5	4.6	560/45R22.5	22.5	4.05
18.00-22.5	22.5	5.25	560/60-22.5	22.5	4.6
18.0R22.5	22.5	4.6	560/60R22.5	22.5	4.6
18-22.5	22.5	5.25	580/65R22.5	22.5	5
18R22.5	22.5	4.6	600/40-22.5	22.5	4.05
205/70-22.5	22.5	1.95	600/50-22.5	22.5	4.4
225/60-22.5	22.5	2	600/50R22.5	22.5	4.4
235/80-22.5	22.5	2.4	600/55-22.5	22.5	4.6
245/75-22.5	22.5	2.4	620/40R22.5	22.5	4.2
255/70-22.5	22.5	2.4	620/50R22.5	22.5	4.6
255/80-22.5	22.5	2.6	650/50-22.5	22.5	4.8
265/70-22.5	22.5	2.5	650/50R22.5	22.5	4.8
265/75-22.5	22.5	2.6	700/40-22.5	22.5	4.6
275/70-22.5	22.5	2.6	700/50-22.5	22.5	5
275/80-22.5	22.5	2.8	700/50R22.5	22.5	5
295/60-22.5	22.5	2.6	710/40-22.5	22.5	4.6
295/70-22.5	22.5	2.8	710/45-22.5	22.5	4.8
295/75-22.5	22.5	2.9	710/45R22.5	22.5	4.8
295/80-22.5	22.5	3	750/45R22.5	22.5	5
305/75-22.5	22.5	3	8.00-22.5	22.5	2.2
315/60-22.5	22.5	2.8	8-22.5	22.5	2.2
315/70-22.5	22.5	3	9.00-22.5	22.5	2.5
315/80-22.5	22.5	3.15	9-22.5	22.5	2.5

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de





construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 23"			Rin 24"		
23-23	23	6.75	14.9-24	24	4.6
Rin 23.5"			14-24	24	4.2
23.00-23.5	23.5	6.75	15.00-24	24	4.6
Rin 24"			15.5/80-24	24	4.2
9-24	24	2.7	15.5-24	24	4.8
10-24	24	3.0	15-24	24	4.6
11-24	24	3.3	16.00-24	24	4.8
12-24	24	3.6	16.00R24	24	4.4
10.00-24	24	3	16.50/80-24	24	4.4
10.00R24	24	2.7	16.50/85-24	24	4.6
11.00-24	24	3.3	16.50-24	24	5
11.20/10-24	24	3.3	16.5-24	24	5
11.20-24	24	3.45	16.90-24	24	5.2
11.2-24	24	3.45	16.90R24	24	4.6
11.25-24	24	3.45	16.9-24	24	5.2
11.2R24	24	3.15	16.9R24	24	4.6
11.40-24	24	3.45	16-24	24	4.8
11.50-24	24	3.45	17.00/80-24	24	4.6
11.5-24	24	3.45	17.50-24	24	5.2
12.00/10.00-24	24	3.3	17.5-24	24	5.2
12.00/8.00-24	24	3	17.5L-24	24	4.8
12.00-24	24	3.6	17.5LR24	24	4.4
12.00R24	24	3.3	18.00-24	24	5.5
12.4/11-24	24	3.6	18.30-24	24	5.5
12.40-24	24	3.75	18.40-24	24	5.5
12.4-24	24	3.75	18.4-24	24	5.5
13.00-24	24	3.9	18-24	24	5.5
13.6/12-24	24	3.9	19.40-24	24	6
13.60-24	24	4.2	19.4-24	24	6
13.6-24	24	4.2	19.50-24	24	6
13.6R24	24	3.75	19.5-24	24	6
13-24	24	3.9	19.5LR24	24	4.8
14.00/10.00-24	24	3.6	20.00-24	24	6
14.00-24	24	4.2	21.00-24	24	6.5
14.00R24	24	3.75	21-24	24	6.5
14.9/13-24	24	4.2	22-24	24	6.8
14.90/13.-24	24	4.2	24-24	24	7.2
14.90-24	24	4.6	255/70-24	24	2.6

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de





construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 24"			Rin 24"		
280/85R24	24	3.15	540/65-24	24	5
320/70-24	24	3.3	540/65R24	24	5
320/70R24	24	3.3	540/70-24	24	5.2
320/75-24	24	3.3	560/65-24	24	5.2
320/85-24	24	3.6	7.20-24	24	2.1
320/85R24	24	3.6	7.2-24	24	2.1
340/85-24	24	3.75	7.50-24	24	2.2
340/85R24	24	3.75	7.5-24	24	2.2
360/70-24	24	3.6	8.3/8-24	24	2.4
360/70R24	24	3.6	8.30-24	24	2.5
380/70-24	24	3.75	8.3-24	24	2.5
380/70R24	24	3.75	9.00-24	24	2.7
380/85-24	24	4.2	9.50/9-24	24	2.8
380/85R24	24	4.2	9.50-24	24	2.9
385/95R24	24	4.4	9.50R24	24	2.6
400/70-24	24	3.9	9.5-24	24	2.9
400/80-24	24	4.2	9.5R24	24	2.6
405/70-24	24	4.05	Rin 24.5"		
405/70R24	24	4.05	11.00-24.5	24.5	3.45
420/65R24	24	4.05	12.00-24.5	24.5	3.75
420/70-24	24	4.2	13.50-24.5	24.5	4.2
420/70R24	24	4.2	13.5-24.5	24.5	4.2
420/85R24	24	4.6	13.56-24.5	24.5	4.2
440/65R24	24	4.2	15.00-24.5	24.5	4.6
440/70R24	24	4.4	18.00-24.5	24.5	5.5
440/80-24	24	4.6	275/80-24.5	24.5	3
440/80R24	24	4.6	285/75-24.5	24.5	3.15
445/70R24	24	4.4	285/80-24.5	24.5	3.15
455/70R24	24	4.4	295/75-24.5	24.5	3.15
460/70-24	24	4.6	305/75-24.5	24.5	3.3
460/70R24	24	4.6	355/75-24.5	24.5	3.75
480/65-24	24	4.6	Rin 25"		
480/65R24	24	4.6	12-25	25	3.8
480/70-24	24	4.8	1050/50-25	25	8
480/70R24	24	4.8	11.00-25	25	3.45
495/70R24	24	4.8	12.00-25	25	3.75
500/70-24	24	4.8	13.00-25	25	4.2
500/70R24	24	4.8	14.00-25	25	4.4

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de





construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 25"			Rin 25"		
14.00R25	25	3.9	550/65-25	25	5.25
15.50-25	25	5	600/65R25	25	5.75
15.5-25	25	5	61x18.00-25	25	5.75
15.5R25	25	4.4	650/65-25	25	6.25
16.00-25	25	5	650/65R25	25	6.25
17.50-25	25	5.5	66x43.00-25	25	8
17.5-25	25	5.5	66x44.00-25	25	8
17.5R25	25	5	67x34.00-25	25	7.75
18.00-25	25	5.8	705/65-25	25	6.75
18.00R25	25	5	705/70-25	25	7
20.50-25	25	6.5	750/65-25	25	7
20.5-25	25	6.5	750/65R25	25	7
20.5R25	25	5.8	755/70-25	25	7.5
21.00-25	25	6.8	800/50-25	25	6.5
22.00/65-25	25	5.5	850/65-25	25	8
22.00-25	25	7	Rin 26"		
23.00/90-25	25	6.75	12.40-26	26	4.2
23.50-25	25	7.5	12.4-26	26	4.2
23.5-25	25	7.5	13.60-26	26	4.4
23.5R25	25	6.5	13.6-26	26	4.4
24.00-25	25	7.5	14.90-26	26	5
25.00/65-25	25	6	14.90R26	26	4.4
26.50-25	25	8.25	14.9-26	26	5
26.5-25	25	8.25	14.9R26	26	4.4
26.5R25	25	7.25	15-26	26	5.00
29.50-25	25	9.2	16.90-26	26	5.5
29.5R25	25	8	16.90R26	26	5
385/95R25	25	4.6	16.9-26	26	5.5
40.50/75-25	25	10.25	16.9R26	26	5
445/80-25	25	5	18.00-26	26	6
445/80R25	25	5	18.4/15-26	26	5.5
445/95-25	25	5.5	18.40-26	26	6
445/95R25	25	5.5	18.40R26	26	5.5
505/95R25	25	6	18.4-26	26	6
525/80-25	25	5.75	18.4R26	26	5.5
525/80R25	25	5.75	18-26	26	6
525/95-25	25	6.25	23.10-26	26	7.5
54x37.00-25	25	6.5	23.1-26	26	7.5

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y





recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 26"			Rin 28"		
23.50-26	26	7.75	12.4-28	28	4.4
24.00-26	26	8	12.4R28	28	4.05
28.00-26	26	9.25	13.60/78-28	28	4.4
28.1-26	26	9.25	13.60-28	28	4.8
28-26	26	9.25	13.60R28	28	4.4
28L-26	26	8	13.6-28	28	4.8
420/85-26	26	5	13-28	28	4.6
420/85R26	26	5	14.90/78-28	28	4.6
480/70-26	26	5.25	14.90-28	28	5.25
480/70R26	26	5.25	14.9-28	28	5.25
480/80-26	26	5.5	14-28	28	5
54x31.00-26	26	6.25	15.00-28	28	5.25
57x31.00-26	26	6.5	15-28	28	5.25
580/70-26	26	6	16.5/85-28	28	5.5
620/75-26	26	6.75	16.50/85-28	28	5.5
66x43.00-26	26	8.25	16.9/14-28	28	5.5
67x34.00-26	26	8	16.90/14-28	28	5.5
750/55-26	26	6.75	16.90-28	28	6
VF620/70R26	26	6.5	16.9-28	28	6
Rin 26.5"			16.9R28	28	5.25
600/55-26.5	26.5	5.75	17.00-28	28	6
600/55R26.5	26.5	5.75	17-28	28	6
620/55R26.5	26.5	5.75	18.40-28	28	6.5
650/55R26.5	26.5	6	18.4-28	28	6.5
650/65R26.5	26.5	6.5	21.00-28	28	7.5
700/50-26.5	26.5	6.25	280/85R28	28	3.6
710/50R26.5	26.5	6.25	320/70-28	28	3.9
750/45R26.5	26.5	6.25	320/70R28	28	3.9
800/45-26.5	26.5	6.5	320/85R28	28	4.2
800/45R26.5	26.5	6.5	340/85R28	28	4.4
Rin 28"			360/70-28	28	4.2
11.20/78-28	28	3.6	360/70R28	28	4.2
11.20-28	28	3.9	380/70-28	28	4.6
11.2-28	28	3.90	380/70R28	28	4.6
11.25-28	28	4.1	380/85-28	28	5
11.2R28	28	3.6	380/85R28	28	5
11.90-28	28	4.2	420/70-28	28	5
12.40/78-28	28	3.9	420/70R28	28	5

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y





recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 28"			Rin 29"		
420/85-28	28	5.5	875/65-29	29	9.5
420/85R28	28	5.5	Rin 30"		
440/65R28	28	5	4-30	30	1.3
440/80-28	28	5.5	6-30	30	2.2
440/80R28	28	5.5	14.90R30	30	5.25
480/65-28	28	5.5	14.9-30	30	5.75
480/65R28	28	5.5	16.9/14-30	30	5.75
480/70-28	28	5.5	16.90-30	30	6.5
480/70R28	28	5.5	16.90R30	30	5.75
540/65-28	28	6	16.9-30	30	6.5
540/65R28	28	6	17.00-30	30	6.5
540/75R28	28	6.5	17-30	30	6.5
580/70-28	28	6.5	18.40-30	30	7
600/65-28	28	6.5	18.4-30	30	7
600/65R28	28	6.5	18.4R30	30	6.25
600/70R28	28	6.75	21.00/80-30	30	7
8.30/8-28	28	2.9	21.00-30	30	8
8.30-28	28	2.9	21-30	30	8
8.3-28	28	2.9	23.10-30	30	7.75
9.5-28	28	3.3	23.1-30	30	7.75
Rin 29"			380/85-30	30	5.25
21.00-29	29	7.75	380/85R30	30	5.25
21-29	29	7.75	4.00-30	30	1.3
24.00-29	29	8.75	420/70-30	30	5.25
24.00R29	29	7.75	420/70R30	30	5.25
24-29	29	8.75	420/85R30	30	5.75
26.50-29	29	9.75	420/90-30	30	6
26.50R29	29	8.5	460/85R30	30	6.25
26.5-29	29	9.75	480/70-30	30	6
29.50-29	29	10.75	480/70R30	30	6
29.50R29	29	9.25	480/80-30	30	6.5
29.5-29	29	10.75	480/85-30	30	6.5
30.00/65-29	29	8.5	520/70-30	30	6.5
32.25R29	29	10.25	520/70R30	30	6.5
33.25-29	29	12	540/65-30	30	6.5
33.25R29	29	10.50	540/65R30	30	6.5
775/65-29	29	8.5	6.00-30	30	2.2
800/65-29	29	8.75	6.3-30	30	2.3

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y





recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 30"			Rin 32"		
600/70-30	30	7.25	800/65-32	32	9.75
600/70R30	30	7.25	800/65R32	32	9.75
620/75-30	30	7.75	800/70R32	32	10.25
67x30.00-30	30	8.5	9.50/9-32	32	3.75
67x34.00-30	30	8.75	9.50-32	32	3.9
7.20-30	30	2.7	9.5-32	32	3.9
7.2-30	30	2.7	900/55-32	32	9.75
9.50-30	30	3.6	900/60-32	32	10.25
9.5-30	30	3.6	900/65-32	32	10.75
Rin 30.5"			IF800/70R32	32	10.25
600/60R30.5	30.5	7	Rin 33"		
600/65-30.5	30.5	7.25	18.00-33	33	7.5
650/65R30.5	30.5	7.75	18.00R33	33	6.75
710/50R30.5	30.5	7.25	18-33	33	7.5
750/60R30.5	30.5	8.25	21.00R33	33	7.75
800/45R30.5	30.5	7.8	27.00-33	33	11.25
850/50R30.5	30.5	8.5	27.00R33	33	9.75
Rin 32"			27-33	33	11.25
12.4/11-32	32	4.8	30.00/65R33	33	9.75
12.40-32	32	5	30.00-33	33	12.5
12.4-32	32	5	30-33	33	12.5
16.90-32	32	6.75	33.50-33	33	13.75
210/95R32	32	3.3	33.5-33	33	13.75
230/95R32	32	3.6	33.65R33	33	12
24.50-32	32	9.75	35.00/65-33	33	11
24.5-32	32	9.75	35/65-33	33	11
30.00-32	32	12	35/65R33	33	11
30.50-32	32	12.25	37.50-33	33	11.5
30.5-32	32	12.25	37.50R33	33	13.5
30-32	32	12	37.5-33	33	15.5
320/85R32	32	4.8	875/65R33	33	11
33.50-32	32	13.5	Rin 33.5"		
35.50-32	32	14.25	13.00-33.5	33.5	5.5
650/75-32	32	8.75	Rin 34"		
68x50.00-32	32	10.25	11.20-34	34	4.8
73x44.00-32	32	10.75	11.2-34	34	4.8
8.30-32	32	3.3	12.40-34	34	5.25
8.3-32	32	3.3	14.90-34	34	6.5

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y





recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 34"			Rin 35"		
14-34	34	6	21.00-35	35	9.25
16.90/78-34	34	6.5	21.00R35	35	9.25
16.90-34	34	7.25	21-35	35	9.25
16.9-34	34	7.25	24.00-35	35	10.5
16.9R34	34	6.5	24.00R35	35	9.25
18.40-34	34	8	24-35	35	10.5
18.4-34	34	8	29.50-35	35	13
18.4R34	34	7	29.50R35	35	11.25
18.50-34	34	8	29.5-35	35	13
18.5-34	34	8	33.25-35	35	14.5
20.80-34	34	9	33.25R35	35	12.75
20.80R34	34	8	37.25-35	35	16.25
23.10-34	34	10	Rin 36"		
23.10R34	34	8.75	4-36	36	1.65
290/95-34	34	4.8	11.20-36	36	5.25
320/85-34	34	5	11.2-36	36	5.25
380/85-34	34	6	12.40-36	36	5.75
380/85R34	34	6	12.4-36	36	5.75
385/85-34	34	6	13.60/78-36	36	5.75
420/70-34	34	6	13.60-36	36	6.25
420/80-34	34	6.5	13.6-36	36	6.25
420/85-34	34	6.5	13.90-36	36	6.25
420/85R34	34	6.5	13.9-36	36	6.25
460/85R34	34	7.25	14.90-36	36	6.75
480/70-34	34	6.75	16.9-36	36	7.75
480/70R34	34	6.75	18.00-36	36	8.25
480/85-34	34	7.5	210/95R36	36	3.75
520/70-34	34	7.25	230/95R36	36	4.05
520/70R34	34	7.25	320/85-36	36	5.5
540/65-34	34	7.25	320/85R36	36	5.5
540/65R34	34	7.25	340/85R36	36	5.75
540/75-34	34	7.75	6.5-36	36	2.9
600/65R34	34	8	7.2-36	36	3.3
600/70R34	34	8.25	8.30-36	36	3.75
650/75-34	34	9.25	8.3-36	36	3.75
710/70-34	34	9.75	9.50-36	36	4.4
710/75-34	34	10	9.5-36	36	4.4

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.



Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 38"			Rin 38"		
4-38	38	1.75	460/85R38	38	8
11.20-38	38	5.5	480/70-38	38	7.75
11.2-38	38	5.5	480/70R38	38	7.75
12.40-38	38	6	480/80-38	38	8.25
12.4-38	38	6	500/85-38	38	8.75
13.60-38	38	6.5	520/70-38	38	8.25
13.60R38	38	6	520/70R38	38	8.25
13.6-38	38	6.5	520/85-38	38	9
13.6R38	38	6	520/85R38	38	9
14.90-38	38	7.25	540/65R38	38	8.25
14.9-38	38	7.25	580/70-38	38	9.25
14-38	38	6.75	580/70R38	38	9.25
15.50-38	38	7.5	600/65-38	38	9
15.5-38	38	7.5	600/65R38	38	9
15.5R38	38	6.75	650/65-38	38	9.75
16.9/14-38	38	7.5	650/65R38	38	9.75
16.90/78-38	38	7.25	650/75-38	38	10.5
16.90-38	38	8	650/75R38	38	10.5
16.90R38	38	7.25	650/85-38	38	11.25
16.9-38	38	8	650/85R38	38	11.25
16.9R38	38	7.25	710/70-38	38	11
16-38	38	7.75	710/70R38	38	11
18.4/15-38	38	8	750/65-38	38	11
18.40/78-38	38	8	8.3-38	38	4.05
18.40-38	38	8.75	800/70-38	38	12.25
18.4-38	38	8.75	800/70R38	38	12.25
18.4R38	38	8	850/80-38	38	14
18-38	38	8.75	9.5-38	38	4.6
20.80-38	38	10	IF800/70R38	38	12.25
20.80R38	38	9	VF710/60R38	38	10.25
20.8-38	38	10	Rin 39"		
270/95R38	38	5	33.50-39	39	16.25
320/85-38	38	5.75	33.50R39	39	14.25
340/85R38	38	6	33.5-39	39	16.25
380/80-38	38	6.5	37.50-39	39	18.25
380/85R38	38	6.75	37.50R39	39	16
400/75R38	38	6.75	37.5-39	39	18.25
420/85R38	38	7.5	40.00/65-39	39	15

Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr



Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros	Neumático	Rin	Litros
Rin 39"			Rin 42"		
40.00-39	39	19.5	900/50R42	42	12.75
40.50/75-39	39	16.5	VF710/60R42	42	11.5
40.5-39	39	19.75	Rin 43"		
41.25/70-39	39	16	24.00-43	43	13
43.50-39	39	21.25	24-43	43	13
45.00/65-39	39	16.5	Rin 44"		
900/50-39	39	11.75	230/95R44	44	5
Rin 40"			8.3-44	44	4.6
7.2-40	40	3.6	9.5-44	44	5.25
Rin 42"			Rin 45"		
12.40-42	42	6.5	45.00/65-45	45	19.5
12.4-42	42	6.5	45/65R45	45	19.5
16.9-42	42	9	45-45	45	25.25
18.40-42	42	9.75	65.00/45-45	45	21.75
18.40R42	42	8.75	Rin 46"		
18.4-42	42	9.8	12.4-46	46	7.25
20.80-42	42	11	13.60-46	46	8
20.80R42	42	10	14.90R46	46	8
20.8-42	42	11	14.9-46	46	8.75
230/95R42	42	4.8	18.40-46	46	10.75
320/80-42	42	6.25	18.40R46	46	9.75
320/90-42	42	6.5	300/95R46	46	6.75
480/80-42	42	9	320/90-46	46	7
480/80R42	42	9	340/85-46	46	7.25
500/85-42	42	9.75	380/85-46	46	8.25
520/85-42	42	10	380/90R46	46	8.25
520/85R42	42	10	420/80-46	46	9.75
620/70-42	42	10.75	480/80-46	46	10
620/70R42	42	10.75	480/80R46	46	10
650/65-42	42	11	500/85-46	46	10.5
650/65R42	42	11	520/85-46	46	11
710/70-42	42	12.25	520/85R46	46	11
710/70R42	42	12.25	620/70-46	46	12
710/75R42	42	12.75	VF380/90R46	46	8.25
8.3-42	42	4.4	Rin 48"		
9.50-42	42	5	18.00R48	48	10
9.5-42	42	5	230/95-48	48	5.5
900/50-42	42	12.75	270/95R48	48	6.25



Tabla de Aplicación OKO México Maquinaria

Tractores, recogedores, vehículos agrícolas, industriales y de construcción, retroexcavadoras, vehículos de carga y recolectores de basura.

Velocidad máxima: 80 km/hr

Capacidad de sellado: hasta 2.0 cm

Neumático	Rin	Litros
Rin 48"		
9.5-48	48	7.75
Rin 49"		
18.00-49	49	11
21.00-49	49	13
21-49	49	13
24.00-49	49	14.75
24-49	49	14.75
27.00-49	49	16.5
27-49	49	16.5
31.00/80-49	49	17
Rin 50"		
17-50	50	10.75
20-50	50	12.5
320/90-50	50	7.75
380/105-50	50	9.5
380/90-50	50	9
480/80-50	50	10.75
480/80R50	50	10.75
Rin 51"		
24-51	51	15.25
27-51	51	17.25
30.00-51	51	19.25
33.00-51	51	21
33-51	51	21
36.00-51	51	23
36-51	51	23
37.50-51	51	24
37.50R51	51	21
37.5-51	51	24
50.00/65-51	51	24.5
50-51	51	31.75
55-51	51	35
65-51	51	41.25
Rin 54"		
12.40-54	54	8.5
320/105-54	54	8.75
320/90-54	54	8.25
380/90-54	54	9.75

[illegible]

